

Ensure that **YOUR PRODUCTS ARE SAFE**

under any

conditions,

- instability
- shape
- transport
- storage



















exposure,

- climate
- corrosion
- abrasion

risks

- theft
- sagging
- customer complaints
- degradation

Benefit from the versatility of the **RIPACK® SERIES 3000**

Packaging	Marine	Bulk items	Containment	Marking	Miscellaneous
 Pallet containing glassware	 Winterizing of recreational boats	 Machines with non-standard dimensions	 Temporary covering spaces	 Application of thermo-plastic road markings	 Flame-treating parts
 Heavy, fragile and unstable load	 Land storage in a marina	 Public works, rolling stock	 Containment for asbestos removal	 Playgrounds	 Thermal weed control
 Multi-shape load on or off-pallet	 Shipyards	 Aeronautics industry, military ...etc	 Protecting a worksite against weather conditions	 Various instructional ground markings	 Adhesive label removal



The film takes on the shape of the product by shrinking under the heat produced by the RIPACK® SERIES 3000. The film forms an excellent protective layer and thermal barrier. The objects are held together and the heat transferred is minimal.

Adopt SHRINKWRAP

Low-density polyethylene (LDPE) is the most common shrinkwrap used. It is available in the form of a film, sheath or cover. The various formats and quantities are adapted to suit all applications. With varied thicknesses, transparent or opaque and colored, the film can be customised to the needs of the shipper.

Distributed By:

new RIPACK® SERIES 3000-70

Offering more

www.ripack.com

Still safe
no risk of burns thanks to
its unique "cold nozzle"
design and always
360° free rotation
with bare hands



More practical
safe and fast hanging by its large
suspension ring well positioned in
the center of gravity

Still robust
aluminum body
and stainless
steel nozzle



Even faster
through its higher
power, save 15% time

More ergonomic
an optional swivel
arm bracket makes it
easier working with
extensions (available 2013)



More productive
no slowdown in production
due to a worn out igniter
easily replaced without tools
in less than a minute by an
incorporated spare igniter

Smarter design
the trigger incorporates an
Allen wrench to unscrew the
body and facilitate maintenance

More comfortable
Ergonomic bi-material
handle for improved grip



Still modular
a range of modular
extensions up to 80" (2M)
allows all applications



Higher
RIPACK 3000-70 comes complete
in a carrying case serving as a
very stable footboard elevating
by 10 inches (27cm) an
operator of 260 lbs. (120 kg)

The RIPACK 3000-70 carrying case contains a shrink-gun with swivel connector, a user manual, a 26 FT. (8M) rubber hose with connectors, a Securipack double security pressure regulator, a wrench for the mounting of regulator and swivel connector.